

## **Oracle® Database**

Oracle SQL Developer Installation Guide

Release 1.0

**B28240-01**

March 2006

Provides information for installing the Oracle SQL Developer tool on Windows2000, Windows XP, Linux, and Mac OS X systems.

SQL Developer Installation Guide, Release 1.0

B28240-01

Copyright © 2006 Oracle. All rights reserved.

Primary Author: Chuck Murray

Contributors: Sharon Kennedy, Baosheng Cai, Kathryn Munn

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software—Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

---

---

# Contents

<b>Preface</b> .....	v
Audience .....	v
Documentation Accessibility .....	v
Related Documents .....	vi
Conventions .....	vi
Third-Party License Information.....	vi
<b>1 Installing Oracle SQL Developer</b>	
1.1 SQL Developer System Requirements .....	1-1
1.2 Installing and Starting SQL Developer .....	1-2
1.2.1 Windows Systems with JDK1.5 .....	1-3
1.2.2 Linux and Mac OS X Systems, and Windows Systems without JDK 5.0 .....	1-3
1.3 Migrating Information from Previous Releases .....	1-4
1.4 SQL Developer User Information Directory .....	1-4
1.5 Database Certification for SQL Developer .....	1-5
1.6 Finding SQL Developer Accessibility Information.....	1-5
1.7 Using a Screen Reader and Java Access Bridge with SQL Developer .....	1-6
1.7.1 Configuring JAWS 3.70 and Access Bridge with SQL Developer .....	1-7
1.8 Uninstalling SQL Developer .....	1-8
1.9 SQL Developer Documentation.....	1-8
1.10 Oracle on the Web.....	1-8

## List of Tables

1-1	Requirements for Windows Systems .....	1-1
1-2	Requirements for Linux Systems.....	1-2
1-3	Requirements for Mac OS X Systems.....	1-2
1-4	Database Certification for SQL Developer .....	1-5

---

---

# Preface

This guide provides information for those installing the Oracle SQL Developer tool on Windows2000, Windows XP, Linux, and Mac OS X systems.

## Audience

This guide is intended for those who need to install the Oracle SQL Developer tool.

## Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

### Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

### Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

### TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

## Related Documents

For conceptual, usage, and reference information about Oracle SQL Developer, see the online help available when you are running SQL Developer.

Oracle error message documentation is only available in HTML. If you only have access to the Oracle Documentation CD, you can browse the error messages by range. Once you find the specific range, use your browser's "find in page" feature to locate the specific message. When connected to the Internet, you can search for a specific error message using the error message search feature of the Oracle online documentation.

Printed documentation is available for sale in the Oracle Store at

<http://oraclestore.oracle.com/>

To download free release notes, installation documentation, white papers, or other collateral, go to the Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at

<http://www.oracle.com/technology/membership>

If you already have a user name and password for OTN, then you can go directly to the documentation section of the OTN Web site at

<http://www.oracle.com/technology/documentation>

## Conventions

The following text conventions are used in this document:

<b>Convention</b>	<b>Meaning</b>
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

## Third-Party License Information

Oracle SQL Developer contains third-party code. Oracle is required to provide the following notices. Note, however, that the Oracle program license that accompanied this product determines your right to use the Oracle program, including the third-party software, and the terms contained in the following notices do not change those rights.

### **Apache Regular Expression Package 1.3**

The Apache Software License, Version 1.1

Copyright © 1999 The Apache Software Foundation

All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

3. The end-user documentation included with the redistribution, if any, must include the following acknowledgement: "This product includes software developed by the Apache Software Foundation (<http://www.apache.org/>)." Alternately, this acknowledgement may appear in the software itself, if and wherever such third-party acknowledgements normally appear.

4. The names "The Jakarta Project", "Jakarta-Regexp", and "Apache Software Foundation" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact [apache@apache.org](mailto:apache@apache.org).

5. Products derived from this software may not be called "Apache" nor may "Apache" appear in their names without prior written permission of the Apache Group.

THIS SOFTWARE IS PROVIDED ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE APACHE SOFTWARE FOUNDATION OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE. This software consists of voluntary contributions made by many individuals on behalf of the Apache Software Foundation. For more information on the Apache Software Foundation, please see <http://www.apache.org/>.

### **Antlr v 2.7.3**

<http://wwwantlr.org/rights.html>

OracleAS TopLink uses Antlr for EJB QL parsing. Antlr (ANother Tool for Language Recognition), is a language tool that provides a framework for constructing recognizers, compilers, and translators from grammatical descriptions containing C++ or Java actions. The ANTLR parser and translator generator is fully in the public domain.

### **JGoodies Looks and Forms**

Copyright © 2003 JGoodies Karsten Lentzsch. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of JGoodies Karsten Lentzsch nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

---



---

# Installing Oracle SQL Developer

Please read the information in this chapter before you install Oracle SQL Developer. This chapter contains the following major sections:

- [Section 1.1, "SQL Developer System Requirements"](#)
- [Section 1.2, "Installing and Starting SQL Developer"](#)
- [Section 1.3, "Migrating Information from Previous Releases"](#)
- [Section 1.5, "Database Certification for SQL Developer"](#)
- [Section 1.6, "Finding SQL Developer Accessibility Information"](#)
- [Section 1.7, "Using a Screen Reader and Java Access Bridge with SQL Developer"](#)
- [Section 1.8, "Uninstalling SQL Developer"](#)
- [Section 1.9, "SQL Developer Documentation"](#)
- [Section 1.10, "Oracle on the Web"](#)

## 1.1 SQL Developer System Requirements

This section describes the recommended CPU, memory, display, disk storage, and other requirements on the supported systems.

---



---

**Note:** The certification process is ongoing for various listed resources, but will be completed before the final production release.

---



---

**Table 1–1 Requirements for Windows Systems**

Resource	Recommended Value or Minimum Value
Operating System	Windows 2000-Service Pack 4 Windows XP-Service Pack 1
CPU Type and Speed	Pentium III 866 MHz or faster
Memory	256 MB RAM
Display	65536 colors, set to at least 1024 X 768 resolution
Hard Drive Space	42 MB if you already have JDK 1.5 110 MB if you do not have JDK 1.5

**Table 1–1 (Cont.) Requirements for Windows Systems**

Resource	Recommended Value or Minimum Value
Java SDK	Sun J2SE 1.5.0_05 for Windows, available at: <a href="http://www.javasoft.com">http://www.javasoft.com</a> (If you do not have this SDK installed, you can use SQL Developer, but you must download and install the kit for Windows systems with no Java SDK or a Sun Java SDK release lower than 1.5.)

**Table 1–2 Requirements for Linux Systems**

Resource	Recommended Value or Minimum Value
Operating System	Red Hat Enterprise Linux 3 or 4 Fedora Core 4 SuSE SLES8
CPU Type and Speed	Pentium III 866 MHz or faster
Memory	256 MB RAM
Display	65536 colors, set to at least 1024 X 768 resolution
Hard Drive Space	110 MB
Java SDK	Sun J2SE 1.5.0_05 for Linux, available at: <a href="http://www.javasoft.com">http://www.javasoft.com</a>

**Table 1–3 Requirements for Mac OS X Systems**

Resource	Recommended Value or Minimum Value
Operating System	Apple Mac OS X Version 10.3
CPU Type and Speed	Dual 1.25 GHz G4/G5 (1 GHz G4 minimum)
Memory	256 MB RAM
Display	"Thousands" of colors
Hard Drive Space	110 MB
Java SDK	Sun J2SE 1.5 release 1, available at: <a href="http://www.apple.com/support/downloads/java2se50release1.html">http://www.apple.com/support/downloads/java2se50release1.html</a>

## 1.2 Installing and Starting SQL Developer

This section contains subsections with instructions for installing SQL Developer on all supported systems.

SQL Developer does not require an installer. To install SQL Developer, you will need an unzip tool. You can download a free, cross-platform unzip tool, Info-Zip, available at <http://www.info-zip.org/>.

---

**Important:** Do not install SQL Developer into any existing ORACLE\_HOME. You will not be able to uninstall it using Oracle Universal Installer.

---

---

---

**Important:** If you are using a *pre-release (Early Adopter)* version of SQL Developer, you **must** unzip the Release 1.0 kit into a different directory than the one used for the pre-release version.

---

---

For Windows systems, there are two kits: one for systems on which the Sun Java SDK release 1.5 is installed, and another for systems with no Java SDK or a Sun Java SDK release lower than 1.5. Be sure to download the appropriate kit.

Before you install SQL Developer, look at the remaining sections of this guide to see if you need to know or do anything else first.

The steps for installing SQL Developer depend on whether or not you will be using it on a Windows system that does not have the Sun Java SDK release 1.5 installed:

- For a Windows system with the Sun Java release 1.5 installed, follow the instructions in [Section 1.2.1](#).
- For all other systems (Linux and Mac OS X systems, and Windows systems with no Java SDK or a Sun Java SDK release lower than 1.5 installed), follow the instructions in [Section 1.2.2](#).

### 1.2.1 Windows Systems with JDK1.5

To install and start SQL Developer on a Windows system on which the Sun Java SDK release 1.5 is installed, follow these steps:

1. Unzip the SQL Developer kit into a folder (directory) of your choice (for example, C:\Program Files). This folder will be referred to as *<sqldeveloper\_install>*.

Unzipping the SQL Developer kit causes a folder named `sqldeveloper` to be created under the *<sqldeveloper\_install>* folder (for example, C:\Program Files\sqldeveloper). It also causes many files and folders to be placed in and under that directory.

2. To start SQL Developer, go to *<sqldeveloper\_install>\sqldeveloper*, and double-click `sqldeveloper.exe`.

After SQL Developer starts, you can connect to any database by right-clicking the Connections node in the Connections Navigator and selecting **New Database Connection**. Alternatively, if you have any exported connections (see [Section 1.3](#) or [Section 1.8](#)), you can import these connections and use them.

You can learn about SQL Developer by clicking **Help**, then **Table of Contents**, and reading the help topics under *SQL Developer Concepts and Usage*.

### 1.2.2 Linux and Mac OS X Systems, and Windows Systems without JDK 5.0

SQL Developer requires that the Sun Java J2SE JDK 5.0 (Update 5 or later) be installed on the system. If you need to install this JDK, go to <http://java.sun.com/j2se/1.5.0/download.jsp> and click the link for downloading JDK 5.0 Update 6 (or the most recent available update).

To install and start SQL Developer, follow these steps:

1. Unzip the SQL Developer kit into a directory (folder) of your choice. This directory location will be referred to as *<sqldeveloper\_install>*.

Unzipping the SQL Developer kit causes a directory named `sqldeveloper` to be created under the `<sqldeveloper_install>` directory. It also causes many files and folders to be placed in and under that directory.

2. To start SQL Developer, go to the `sqldeveloper` directory under the `<sqldeveloper_install>` directory, and do one of the following, as appropriate for your operating system:

On Linux and Mac OS X systems, run `sh sqldeveloper`.

On Windows systems, double-click `sqldeveloper.exe`.

After SQL Developer starts, you can connect to any database by right-clicking the Connections node in the Connections Navigator and selecting **New Database Connection**. Alternatively, if you have any exported connections (see [Section 1.3](#) or [Section 1.8](#)), you can import these connections and use them.

You can learn about SQL Developer by clicking **Help**, then **Table of Contents**, and reading the help topics under *SQL Developer Concepts and Usage*.

## 1.3 Migrating Information from Previous Releases

If you have used a pre-release version of SQL Developer, you may want to preserve database connections that you have been using. To preserve database connections, save your existing database connections in an XML file. To save the connections, right-click the Connections node in the Connections Navigator and select **Export Connections**. After you complete the installation described in this guide, you can use those connections by right-clicking the Connections node in the Connections Navigator and selecting **Import Connections**.

If you want to use any user-defined reports or the SQL history from a pre-release version, see [Section 1.4](#) for information about where these are located.

SQL Developer preferences (specified by clicking Tools and then Preferences) from a previous release cannot currently be saved and used; you must re-specify any desired preferences.

---

---

**Note:** If you want to uninstall your pre-release version of SQL Developer before installing this release, see [Section 1.8, "Uninstalling SQL Developer"](#).

---

---

## 1.4 SQL Developer User Information Directory

SQL Developer stores information about user-defined reports, SQL history, and temporary files created to buffer statements entered in SQL Worksheets. This information is stored in and under the SQL Developer user information directory, which has the following location:

- On Windows systems: the HOME environment variable location, if defined; otherwise the `SQLDEVELOPER_USER_DIR` location, if defined; otherwise `<sqldeveloper_install>\sqldeveloper\jdev\system`
- On Linux and Mac OS X systems: the `SQLDEVELOPER_USER_DIR` location, if defined; otherwise `~/.sqldeveloper`

To specify a non-default `SQLDEVELOPER_USER_DIR` location, do either of the following:

- Set the `SQLDEVELOPER_USER_DIR` environment variable to specify another directory path.
- Edit the `<sqldeveloper_install>/sqldeveloper/jdev/bin/sqldeveloper.conf` file and substitute the desired directory path for `SQLDEVELOPER_USER_DIR` in the following line:

```
SetUserHomeVariable SQLDEVELOPER_USER_DIR
```

If you want to prevent other users from accessing your user-specific SQL Developer information, you must ensure that the appropriate permissions are set on the directory where that information is stored or on a directory above it in the path hierarchy. For example, on a Windows system you may want to ensure that the `sqldeveloper` folder and the `<user-name>\.sqldeveloper` folder under `Documents and Settings` are not shareable; and on a Linux or Mac OS X system you may want to ensure that the `~/ .sqldeveloper` directory is not world-readable.

## 1.5 Database Certification for SQL Developer

---

**Note:** The certification process is ongoing, but will be completed before the final production release.

---

Table 1–4 associates Oracle databases with the SQL Developer features they are certified against. In this table, *Certified* means that the feature is supported on that database, and has passed testing by SQL Developer QA; and *Supported* means that Oracle will address customer issues, but the features are not necessarily tested. The databases shown are all supported, even if not fully certified or working in this release.

**Table 1–4 Database Certification for SQL Developer**

Database Release	Database Certification Status	SQL Developer Database Features	SQL Developer SQL Worksheet	SQL Developer PL/SQL Support
Oracle9i (9.2.0.4)	Full Certification	Certified	Certified	Certified
Oracle Database 10g	Full Certification	Certified	Certified	Certified
Oracle Database Express Edition 10g	Full Certification	Certified	Certified	Certified

SQL Developer has not yet been tested using Oracle Lite (4.0.3).

## 1.6 Finding SQL Developer Accessibility Information

For the latest configuration information or for information on addressing accessibility and assistive technology issues, see the Oracle Accessibility FAQ at <http://www.oracle.com/accessibility/faq.html>.

Also, check the SQL Developer release notes (`readme.txt` file) to see if there are any currently known issues regarding accessibility.

## 1.7 Using a Screen Reader and Java Access Bridge with SQL Developer

To make the best use of our accessibility features, Oracle Corporation recommends the following minimum technology stack:

- Windows 2000 or Windows XP
- Java Sun J2SE 1.5.0\_05
- Sun Java Access Bridge 1.1 or higher
- JAWS 3.70.87, or 5.10 or higher

Follow these steps to set up a screen reader and Java Access Bridge. If you are using JAWS 3.70.87, see the additional configuration information provided after the procedure.

1. Install the screen reader, if it is not already installed. (See the documentation for your screen reader for more information about installation.)
2. Install SQL Developer.
3. Download Java Access Bridge for Windows version 1.1. The file you will download is `accessbridge-1_1.zip`. It is available from <http://java.sun.com/products/accessbridge>. (See the Java Access Bridge documentation available from this Web site for more information about installation and the Java Access Bridge.)
4. After downloading the file, extract (unzip) the contents to a folder, for example, `accessbridge_home`.
5. Install Java Access Bridge by running `Install.exe` from the `<accessbridge_home>\installer` folder.

The installer first checks the SDK version for compatibility, then the Available Java virtual machines dialog displays.

6. Click **Search disks**. Then select to search only the drive that contains the SQL Developer build and the SDK version in the program files directory (if it exists).

The search process can take a long time on a large disk with many instances of SDK or SQL Developer, or when searching multiple disks. However, unless you complete an exhaustive search of your disk, Access Bridge will not be optimally configured, and will not be correctly installed to all of the Java VMs on your system. After selecting the disk to search, click **Search**.

7. Confirm that you want to install the Java Access Bridge into each of the Java virtual machines displayed in the dialog, by clicking **Install in All**.
8. Click **OK** when you see the *Installation Completed* message.
9. Confirm that the following files have been installed in the `Winnt\System32` directory (or the equivalent Windows 2000 or XP directory), or copy them from `<accessbridge_home>\installer\installerFiles` because they must be in the system path in order to work with SQL Developer:

```
JavaAccessBridge.dll
JAWTAccessBridge.dll
WindowsAccessBridge.dll
```

Note that the system directory is required in the `PATH` system variable.

10. Confirm that the following files have been installed in the `<sqldeveloper_install>\jdk\jre\lib\ext` directory, or copy them from `<accessbridge_home>\installer\installerFiles`:

```

access-bridge.jar
jaccess-1_3.jar
jaccess-1_4.jar
JavaAccessBridge.dll
JAWTAccessBridge.dll
WindowsAccessBridge.dll

```

11. Confirm that the file `accessibility.properties` has been installed in the `<sqldeveloper_install>\jdk\jre\lib\ext` directory, or copy it from `<accessbridge_home>\installer\installerFiles`. Confirm that the file `accessibility.properties` includes the following lines:

```

assistive_technologies=com.sun.java.accessibility.AccessBridge
AWT.EventQueueClass=com.sun.java.accessibility.util.EventQueueMonitor
AWT.assistive_technologies=com.sun.java.accessibility.AccessBridge

```

12. Only if you are using JAWS version 3.7, do the following: modify the file `jdev.conf` located in the folder `<sqldeveloper_install>\jdev\bin` to uncomment the `AddVMOption` line, as shown in the following:

```

#
# Prepend patches to the bootclasspath. Currently, rtpatch.jar contains a
# patch that fixes the javax.swing.JTree accessibility problems.
# Uncomment the line below if you need to run SQL DeveloperSQL Developer under
# JAWS.
#
AddVMOption -Xbootclasspath/p:../../jdk/jre/lib/patches/rtpatch.jar

```

13. Start your screen reader.

14. Start SQL Developer.

These steps assume you are running Windows and using a Windows-based screen reader. A console window that contains error information (if any) will open first and then the main SQL Developer window will appear, once SQL Developer has started. Any messages that appear will not affect the functionality of SQL Developer.

### 1.7.1 Configuring JAWS 3.70 and Access Bridge with SQL Developer

The following combinations of Access Bridge file versions are necessary to achieve optimal functionality with JAWS 3.70, since this version of the screen reader uses older Java technology than is used in SQL Developer. There are two stacks of software technology listed below for those who want to use either version 1.0.3 or 1.0.4 of the Access Bridge. Also required in the `system32` directory is a copy of the latest version of the Access Bridge jar file.

#### Access Bridge v. 1.0.3 Configuration for SQL Developer

Place the following files in the `<sqldeveloper_install>\jdk\jre\lib\ext` directory:

```

access-bridge.jar size: 27295 version: access-bridge-1.0.4
JAWTAccessBridge.dll size: 28672 version: AccessBridge-1.0.3
jaccess-1_3.jar size: 43584 version: AccessBridge-1.0.3
jaccess-1_4.jar size: 46597 version: AccessBridge-1.0.3
JavaAccessBridge.dll size: 139264 version: AccessBridge-1.0.3
WindowsAccessBridge.dll size: 77824 version: AccessBridge-1.0.3

```

Place the following file in the `<sqldeveloper_install>\jdk\jre\lib` directory:

```

accessibility.properties size: 353 version: AccessBridge-1.0.3

```

Place the following files in the Windows `system32` directory:

```
JavaAccessBridge.dll size: 155648 version: AccessBridge_1_1_GA
WindowsAccessBridge.dll size: 77824 version: AccessBridge-1.0.3
JAWTAccessBridge.dll size: 28672 version: AccessBridge-1.0.3
```

### Access Bridge v. 1.0.4 Configuration for SQL Developer

Place the following files in the `<sqldeveloper_install>\jdk\jre\lib\ext` directory:

```
access-bridge.jar size: 27295 version: access-bridge-1.0.4
JAWTAccessBridge.dll size: 32768 version: AccessBridge-1.0.4
jaccess-1_4.jar size: 46573 version: AccessBridge-1.0.4
JavaAccessBridge.dll size: 139264 version: AccessBridge-1.0.4
WindowsAccessBridge.dll size: 77824 version: AccessBridge-1.0.4
```

Place the following file in the `<sqldeveloper_install>\jdk\jre\lib` directory:

```
accessibility.properties size: 153 version: AccessBridge-1.0.4
```

Place the following files in the Windows `system32` directory:

```
JavaAccessBridge.dll size: 155648 version: AccessBridge_1_1_GA
WindowsAccessBridge.dll size: 77824 version: AccessBridge-1.0.3
JAWTAccessBridge.dll size: 28672 version: AccessBridge-1.0.3
```

## 1.8 Uninstalling SQL Developer

Before you uninstall SQL Developer, if you plan to install SQL Developer (the same or an updated version) later, you may want to save your existing database connections; and if so, see [Section 1.3](#) before uninstalling.

To uninstall SQL Developer, remove the entire SQL Developer installation directory (that is, the directory named `sqldeveloper` and all directories and files under it in the hierarchy).

If you also want to remove all user-specific SQL Developer information, you should also delete the directory under which that information is stored (that is, the SQL Developer user information directory). For the location of this directory, see [Section 1.4](#).

If you have created a shortcut for SQL Developer, and if you do not plan to install SQL Developer into the same location again, you should remove that shortcut or modify the shortcut properties to reflect the new location.

## 1.9 SQL Developer Documentation

The only SQL Developer user documentation is the online help. To see the help, click the **Help** menu, or click the **Help** button or press the F1 key in relevant contexts while you are using SQL Developer.

As a convenience, the SQL Developer online help topics are also available in a single PDF file, which you can download separately from the SQL Developer kit.

## 1.10 Oracle on the Web

Oracle provides a number of resources on the Web. These are some sites you may find helpful:

- SQL Developer home page (OTN):  
[http://www.oracle.com/technology/products/database/sql\\_developer/](http://www.oracle.com/technology/products/database/sql_developer/)
- SQL Developer discussion forum (OTN):  
<http://forums.oracle.com/forums/forum.jspa?forumID=260>
- Oracle Technology Network (OTN): <http://www.oracle.com/technology/>
- PL/SQL page on OTN: [http://www.oracle.com/technology/tech/pl\\_sql/](http://www.oracle.com/technology/tech/pl_sql/)
- Oracle Accessibility site: <http://www.oracle.com/accessibility/>
- Oracle Corporate site: <http://www.oracle.com/>

