

## ORACLE DUAL PORT QDR INFINIBAND ADAPTER M3

INDUSTRY-LEADING BANDWIDTH, LATENCY, AND I/O CONVERGENCE

### KEY FEATURES

- Two ports of 40 Gb/s InfiniBand
- Guaranteed bandwidth and low latency
- Hardware-based I/O virtualization
- PCI Express® 3.0
- Delivers twice the InfiniBand bandwidth versus previous-generation adapters

### KEY BENEFITS

- Use the full performance of Oracle server and storage systems supporting PCI Express® 3.0 (128 GT/sec, full-duplex bandwidth)
- Use a single high-performance adapter for all server network, storage, and IPC traffic
- Reduce the cost and complexity of server I/O and networking
- Optimize performance of your application and database clusters



*The Oracle Dual Port QDR InfiniBand Adapter M3, a part of Oracle’s InfiniBand and network virtualization portfolios, is designed to provide maximum fabric bandwidth to servers and storage supporting PCI Express® 3.0. The Oracle Dual Port QDR InfiniBand Adapter M3 enables applications to take full advantage of the I/O capabilities integrated into Oracle’s latest servers, doubling the network bandwidth available in high-performance application and server virtualization environments.*

### Overview

High fabric bandwidth, low latency, and RDMA-based network and storage protocols have become critical enablers for delivering leading application performance. InfiniBand, which today delivers 40 Gigabit-per-second connectivity with application-to-application latencies as low as one microsecond, has become a dominant fabric for high-performance enterprise clusters and deployments of virtualized servers. Its ultra-low latency and near-zero CPU utilization for remote data transfers make InfiniBand an ideal fabric for high-performance clustered applications, delivering extreme I/O performance while preserving server resources for application processing. As an integral part of Oracle’s portfolio of high-performance networking products, the Oracle Dual Port QDR InfiniBand Adapter M3 provides low-latency, high-bandwidth I/O services to application clusters running on Oracle servers and storage systems. Service-oriented I/O ensures scalable and granular quality of service for a converged set of data center applications, in both native operating system and virtualized server environments.

### Oracle Dual Port QDR InfiniBand Adapter M3 Specifications

#### Form Factor

- Standard low-profile PCI Express® dimensions

### OS, Hypervisor, and Distribution Support

Oracle's InfiniBand adapters are components of the Oracle server or storage system in which they are installed. See the list of supported option cards for the applicable server or storage system to determine the relevant operating system support for the system and adapter combination.

- Oracle Virtual Networking
- Oracle Solaris
- Oracle Enterprise Linux

For the current list of supported systems, please review the systems I/O support matrices at: <https://wikis.oracle.com/display/SystemsComm/Home>

### Key Applications

- Oracle Virtual Networking
- Cloud and virtual environments
- High-performance storage
- Clustered applications and databases
- Oracle Real Application Clusters (Oracle RAC)
- Real-time data distribution and transaction processing (market data)
- Technical computing

### PCI Express®

- PCIe Base 3.0 compliant, 1.1 and 2.0 compatible
- 2.5 GT/sec, 5.0 GT/sec or 8.0 GT/s link rate x8 (Up to 128 GT/s bidirectional)
- Bracket dimensions are PCI 3.0 CEM compliant: 2.5 in. x 6.6 in.
- SR-IOV

### InfiniBand

- IBTA v1.2.1-compatible design
- 16 million I/O channels
- 10 Gb/sec, 20 Gb/sec, or 40 Gb/sec per port
- 9 virtual lanes: 8 data plus one management
- MTU: 4,096 bytes
- Interoperates with Oracle Virtual Networking and Oracle's InfiniBand switches
- Interoperates with Oracle's InfiniBand copper and optical cabling solutions

### Connections

- The adapter supports two 4x QDR InfiniBand ports (QSFP+ connectors); each 4x port supports 10 Gb/sec traffic on SDR, 20 Gb/sec traffic on DDR, and 40 Gb/sec on QDR.

### Protocol Support

- Oracle Virtual Networking
- RDS, TCP/UDP, IPoIB, SDP, RDS
- EoIB, SRP, iSER, NFS RDMA,
- uDAPL
- MPI
- OpenFabrics User Verbs

### Regulatory Compliance

Agency and Safety Approvals

- FCC Part 15, Subpart B, Class A (U.S.)
- ICES-003 Class A (Canada)

- VCCI Class A (Japan)
- CE Mark (EU), consisting of:
  - EN55022:2010, Class A
  - EN55024:2010
- CISPR 22:2008 (International)
- UL 60950-1:2nd Edition (cURus – U.S.)
- CSA 22.2 No 60950-1-07 (cURus - Canada)
- CB Report and Certificate to IEC 60950-1:2005 (International)
- EU RoHS Compliant (Directive 2011/65/EU)
- WEEE (Directive 2002/96/EC)

### Operating Environment

- Operating voltage: 12 V, 3.3 V
- Operating temperature: 0° C to 55° C
- Maximum power: QDR low-profile PCIe adapter: 9.35 W with passive copper cables, 12.35 W with active optical cables

### Transceivers and Cables

- Oracle supplies InfiniBand cables and transceivers that are supported with the Oracle Dual Port QDR InfiniBand Adapter M3. For more information, see the Oracle Dual Port QDR InfiniBand Adapter M3 FAQ at:

<http://www.oracle.com/us/products/networking/infiniband/dual-port-qdr-ib-m3/dual-port-qdr-infiniband-m3-faq-2004727.pdf>

## Warranty

For more information, visit [oracle.com/sun/warranty](http://oracle.com/sun/warranty) for Oracle's global warranty

## Services

Only Oracle offers single point of accountability and complete, integrated support for the entire Oracle stack including 24/7 hardware service, expert technical support, proactive tools, and software updates. Visit [oracle.com/sun/services](http://oracle.com/sun/services) for information on Oracle's service program offerings for Sun products

## Contact Us

For more information about the Oracle Dual Port QDR InfiniBand Adapter M3, please visit [oracle.com](http://oracle.com) or call +1.800.ORACLE1 to speak to an Oracle representative.



Copyright © 2013, Oracle and/or its affiliates. All rights reserved.

This document is provided for information purposes only, and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose.

We specifically disclaim any liability with respect to this document, and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group. 0113

**Hardware and Software, Engineered to Work Together**