

SUN BLADE X6450 SERVER MODULE

KEY FEATURES

WORLD-CLASS, FOUR-SOCKET PERFORMANCE

FEATURES

- Intel Xeon processors 7000 series provide up to 24 processing cores of highly scalable performance
- Up to 192 GB of memory in 24 DIMM slots per server module—50 percent more memory capacity than competing blade servers
- No disks, fans, or power supply units on server module
- All I/O is off server module, hot pluggable, externally accessible—plus only Sun Blade server modules offer unique I/O per blade for maximum configuration flexibility
- Operating system flexibility—runs Solaris 10 OS, Linux, Windows, or VMware
- Supported by Sun Blade 6000 and Sun Blade 6048 modular systems
- Sun Blade transparent management—direct management of each server module for seamless integration into existing management infrastructure
- Flash technology instantly speeds I/O intensive application performance

Oracle's four-socket Sun Blade X6450 server module leverages two or four Intel Xeon processors 7000 series for blazing-fast performance. A powerful system that enables you to do more with less, the Sun Blade X6450 server module is ideal for virtualization and server consolidation, high-performance computing (HPC), and database and enterprise applications, due to its enhanced speed and efficiency. It can provide up to 11 TFLOPS of peak performance per fully populated Sun Blade 6048 modular system, at 1,152 cores per rack—that's up to 71 percent more compute power than competing blade servers.



Sun Blade X6450 server module provides world-class, four-socket performance.

High-Performance Blade Server

The innovative diskless configuration of the Sun Blade X6450 server module is designed to boot from SAN or CompactFlash (CF), which provides greater security while consuming less power. With up to 192 GB of memory and 24 DIMM slots per server module, it has 50 percent greater memory capacity than rival blade servers.

The Sun Blade X6450 server module comes with internal storage and integrated network connectivity. This scalable server module provides maximum ROI and gives you the headroom you need to expand your data center along with your business—without adding complexity. The Sun Blade X6450 server module is available with the Sun Blade 6000 and 6048 modular systems. With hardware-level virtualization, the Sun Blade X6450 server module offers enhanced energy



efficiency to reduce power and cooling costs, and its denser design can help reduce size without compromising performance. This versatile system runs Oracle's Solaris, Linux, Windows, and VMware operating systems, to ease standardization on a single hardware platform. It also enables you to run your existing 32-bit applications on the same hardware as you upgrade to next-generation 64-bit applications.

Because it fits so much processing power into a compact footprint, the Sun Blade X6450 server module enables you to maximize availability with redundant deployment in the data center.

Sun Blade X6450 Server Module Specifications

This server module also provides streamlined local or remote management and monitoring via a dedicated service processor. It further enables enterprise-class reliability through ECC and Chipkill technology, along with redundant, hot-swappable power supplies and fans that are standard in the Sun Blade 6000 and 6048 modular systems.

The eco-efficient, highly serviceable system scales up, out, and within. It provides integrated networking connectivity and enhanced cost-effectiveness, and can be combined with Oracle's rich portfolio of Sun software, storage, and service offerings to bring new competitive advantages to your data center.

Architecture	
Processors	<ul style="list-style-type: none"> Two or four Intel Xeon processors 7000 series, with up to six cores and up to 16 MB cache per CPU Server module provides choice of 50 W, 65 W, 80 W, or 90 W per processor socket for optimal power efficiency
Main Memory	<ul style="list-style-type: none"> Support for 2GB, 4GB, and 8GB PC2-5300 fully buffered DIMMs at 667MHz 24 DIMM slots support up to 192GB of memory per server module
Interfaces	
Network	<ul style="list-style-type: none"> Two 10/100/1000 Base-T Ethernet ports using the Intel 82563EB Gigabit Ethernet (GbE) transceiver One dedicated 10/100 Base-T Ethernet port for the management network
Storage	<ul style="list-style-type: none"> Four SAS interfaces to the midplane, two to each Network Express Module (NEM) IDE CompactFlash Module Interface (Type I) Internal SATA solid-state drive (SSD) interface
Graphics	Embedded graphics using the AST2000 video controller with 128 MB of shared SDRAM

Interfaces (continued)	
Midplane I/O	
<ul style="list-style-type: none"> • Two x8 PCI Express (PCIe) busses, one x8 PCIe bus to each of the PCIe ExpressModules (EMs) • Two x4 PCIe busses, one x4 bus to each the NEMs • Four 3 Gb/sec SAS interfaces, two to each NEM • Two 10/100/1000GbE interfaces, one per NEM • 10/100 Ethernet management port to Chassis Monitoring Module (CMM) • Available RAID 5 support with Sun PN X4620A • Available 10 GbE performance with Sun PN X1029A-Z 	
Front Panel I/O (available via dongle cable)	
<ul style="list-style-type: none"> • VGA graphics (DB-15 connector) • Serial console server-to-server module on-board lights-out management • Dual USB ports for keyboard, mouse, or storage 	
Software	
Operating Systems	
<ul style="list-style-type: none"> • Solaris 10 Operating System • Red Hat Enterprise Linux Advanced Server • SUSE Linux Enterprise Server 	<ul style="list-style-type: none"> • Windows Server 2003, Standard and Enterprise Editions (32-bit/64-bit) • Windows Server 2008, Datacenter Edition • VMware ESX Server
Networking	
<ul style="list-style-type: none"> • ONC and ONC+ • NFS and WebNFS • TCP/IP • SunLink • OSI 	<ul style="list-style-type: none"> • MHS • IPX/SPX • SMB Technologies • XML
Management	
<p>Advanced on-board management and monitoring, enabled by an embedded Integrated Lights Out Manager (ILOM) service processor, provides the following:</p> <ul style="list-style-type: none"> • DMTF-style command line • Support for SSH 2.0, HTTPS, RADIUS, LDAP, and MS Active Directory • Browser-based GUI • IPMI 2.0; SNMP v1, v2c, v3 • Local and remote KVM (keyboard, video, mouse) and media (CD, floppy, USB) <p>Optional Sun xVM Ops Center: Generation of profiles to ensure compliance and compliance reporting, discovery and registration of data center assets, job scheduling to perform network tasks, system provisioning, and updates to Linux and the Solaris OS</p>	
Dimensions	
<ul style="list-style-type: none"> • Height: 44.45 mm (1.75 in.) • Width: 327.15 mm (12.88 in.) • Depth: 496.82 mm (19.56 in.) • Weight: 6.91 kg (15.24 lbs.) empty—no memory, REM, or FEM • Weight: 7.97 kg (17.58 lbs.) fully configured 	

Warranty

Visit oracle.com/sun/warranty for Oracle's global warranty support information on Sun products.

Services

Visit oracle.com/sun/services for information on Oracle's service program offerings for Sun products.

Contact Us

For more information about Oracle's Sun Blade X6450 server module, please visit oracle.com/sun or call +1.800.786.0404 to speak to an Oracle representative.



Oracle is committed to developing practices and products that help protect the environment

Copyright © 2009, Oracle and/or its affiliates. All rights reserved.

This document is provided for information purposes only and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. UNIX is a registered trademark licensed through X/Open Company, Ltd. 0909