


Oracle Functions

Level 100

KD Singh

Oracle Cloud Infrastructure

October, 2019



Safe harbor statement

The following is intended to outline our general product direction. It is intended for information purposes only, and may not be incorporated into any contract. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions.

The development, release, timing, and pricing of any features or functionality described for Oracle's products may change and remains at the sole discretion of Oracle Corporation.



Objectives

After completing this lesson, you should be able to understand:

Overview and key features

Core concepts

IAM policies

How Functions work?

Functions metrics


Common use-cases of Functions

Demo


Serverless Compute – Functions-as-a-service (FaaS)




Bare Metal



Virtual machines



Containers



Functions

Code
App Container
Language Runtime
Operating System
Hardware

Code
App Container
Language Runtime
Operating System

Code
App Container

Code

Serverless is a category of cloud services that raises the abstraction level so that developers don't need to think about servers, VMs or other IaaS components

Oracle Functions

Functions-as-a-Service


Oracle Cloud Integrated

Container Native

Open Source Engine

Multi-tenant

Secure



No Lock-in

- Built on open-source Fn Project and Docker
- Platform independent: laptop, server, cloud

Autonomous

- Platform auto-scales functions
- No servers to provision, manage

Pay Per Use

Pay for execution, not for idle time

Functions Overview



Push container
to registry



Configure function
trigger




Code runs only
when triggered




Pay for code
execution time only

Function Triggers



Function Integrations



Example Java Function

```
1 package com.example.fn;  
2  
3 public class HelloFunction {  
4  
5     public String handleRequest(String input) {  
6         String name = (input == null || input.isEmpty()) ? "world" : input;  
7  
8         return "Hello, " + name + "!";  
9     }  
10 }  
11 }
```

Function Development Kits (FDKs)

Simply write a `handler` function that adheres to the FDK's interface and the FDK will provide the input to your function, as well as deal with returning the proper output format.
FDKs make it easy to write functions



Oracle Functions Concepts - Applications

In Oracle Functions, an application is:

- a logical grouping of functions
- a common context to store configuration variables that are available to all functions in the application

When you define an application in Oracle Functions, you specify the subnets in which to run the functions in the application.

Oracle Functions shows applications and their functions in the Console.

Oracle Functions Concepts - Functions

In Oracle Functions, functions are:

- small but powerful blocks of code that generally do one simple thing
- grouped into applications
- stored as Docker images in a specified Docker registry
- invoked in response to a CLI command or signed HTTP request

When you deploy a function to Oracle Functions using the Fn Project CLI, the function is built as a Docker image and pushed to a specified Docker registry.

Oracle Functions Concepts - Invocations

In Oracle Functions, a function's code is run (or executed) when the function is called (or invoked). You can invoke a function that you've deployed to Oracle Functions from:

- The Fn Project CLI.
- The Oracle Cloud Infrastructure SDKs.
- Signed HTTP requests to the function's invoke endpoint. Every function has an invoke endpoint.
- Other Oracle Cloud services (for example, triggered by an event in the Events service) or from external services.

When a function is invoked for the first time, Oracle Functions pulls the function's Docker image from the specified Docker registry, runs it as a Docker container, and executes the function. If there are subsequent requests to the same function, Oracle Functions directs those requests to the same container. After a period being idle, the Docker container is removed.



Oracle Functions Concepts - Triggers

A trigger is the result of an action elsewhere in the system, that sends a request to invoke a function in Oracle Functions.

For example, an event in the Events service might cause a trigger to send a request to Oracle Functions to invoke a function.

Alternatively, a trigger might send regular requests to invoke a function on a defined, time-based schedule.

A function might not be associated with any triggers, or it can be associated with one or multiple triggers.



IAM Policies required to work with Oracle Functions

Select the tenancy's root compartment, and create a new policy with the following two policy statements for the Oracle Functions service:

Allow service FaaS to read repos in tenancy

Allow service FaaS to use virtual-network-family in compartment <compartment-name>

If one or more Oracle Functions users is not a tenancy administrator, add the following policy statements to the new policy:

Allow group <group-name> to manage repos in tenancy


Allow group <group-name> to use virtual-network-family in compartment <compartment-name>

Allow group <group-name> to manage functions-family in compartment <compartment-name>

Allow group <group-name> to read metrics in compartment <compartment-name>


How Oracle Functions works?

Deploying a Function



How Oracle Functions works?

Invoking a Function



Functions Metrics

- **FunctionExecutionDuration**: Total function execution duration in milliseconds
- **FunctionInvocationCount**: Total number of function invocations
- **FunctionResponseCount**: Total number of function responses
 - **Errors**: The number of times a function failed
 - **Throttles**: The number of requests to invoke a function that returned a '429 Too Many Requests' error in the response

Functions Use Cases

Use Cases – “*Run Code in Response to Events*”




Glue Cloud
Services, Event-
driven



Web, Mobile, IoT
Backends




Real-time File,
Stream
Processing




DevOps, Batch
Processing

Use Functions to Glue Cloud Services



Infrastructure Event Driven Architectures




ATP = Autonomous Transaction Processing


ADW = Autonomous Data Warehouse




Automate Corporate Security Actions



Network Security Analysis




Automate Database Environment Setup



- Functions runs scripts to create schemas, tables and import golden data.
- Notifications triggers email and PagerDuty alerts.


Demo: Integrating an OCI Service event with Oracle Functions



Summary

- Fully managed event ingestion and routing platform that enables users to automatically detect changes on their resources and act upon them.
- Customers simply pick the services they care about, the type of event they want to monitor, and the actions they want to take.
- **Free** service with a native **CNCF** cloudevents support.
- Integrated with IAM and Monitoring
- Accessible through REST APIs, OCI console, SDKs, CLI, Terraform
- Roadmap
 - Support for custom events via OSS
 - Support for “Advanced” flow, which allows users to input custom verbose json for more complex rules.





Oracle Cloud always free tier:
oracle.com/cloud/free/

OCI training and certification:
cloud.oracle.com/en_US/iaas/training
cloud.oracle.com/en_US/iaas/training/certification
education.oracle.com/oracle-certification-path/pFamily_647

OCI hands-on labs:
ocitraining.qloudable.com/provider/oracle

Oracle learning library videos on YouTube:
youtube.com/user/OracleLearning

