



Technical Documentation for EU regulation 2019/424 for Servers and Data Storage Products from (ErP) Directive 2009/125/EC EcoDesign Requirements for Energy Related Products

Oracle America Inc.
500 Oracle Parkway
Redwood Shores, CA 94065 USA
www.oracle.com

Product Type	Rack-mount Server
Name/Address of Manufacturer	Oracle America Inc...
Product Model Number	X8-2 Server, all models as defined in the DoC
Compliance Model Number	PU1SL
Year of Manufacture	2019
PSU Efficiency	10% Load: 91.85% 20% Load: 94.2% 50% Load: 95.41% 100% Load: 94.33%
Power Factor at 50% load	0.99
Power Supply rated power output	1200W
Idle State Power	Low-end configuration: 127.0 W High-end configuration: 158.0 W
Additional Idle Power Allowances	Low-end configuration, list of all components : 1pcs Intel Xeon Gold 5222 CPU 192GB Memory 2pcs HDD 2pcs SSD 2pcs PSU 2pcs on-board Ethernet 1 Gb/s Active ports and additional 2pcs on-board Ethernet 25 Gb/s Active ports High-end configuration, list of all components : 2pcs Intel Xeon Platinum 8260 CPU 384GB Memory 2pcs SSD 2pcs PSU 2pcs on-board Ethernet 1 Gb/s Active ports and additional 2pcs on-board Ethernet 25 Gb/s Active ports



Technical Documentation for EU regulation 2019/424 for Servers and Data Storage Products from (ErP) Directive 2009/125/EC EcoDesign Requirements for Energy Related Products

Oracle America Inc.
500 Oracle Parkway
Redwood Shores, CA 94065 USA
www.oracle.com

Maximum Measured Power at low-end configuration	223.7 W
Maximum Measured Power at high-end configuration	528.1 W
Declared Operating Condition Class	A2
Idle power consumption at high boundary of declared operating condition	Low-end Configuration: 129.0 W High-end Configuration: 175.0 W
Active State Efficiency	Low-end Configuration: 11.8 High-end Configuration: 35.2
Products disassembly for service	Oracle products are designed to be readily disassembled for Service. See product Service Manual for details.
Content of Cobalt in batteries and Neodymium in HDDs	Cobalt weight is less than 5g Neodymium Content HDDs with a capacity of 1.2G, 8TB and 10TB fall within 5g & 25g HDDs with a capacity of 14TB are less than 5g.
Secure deletion functionality	See Note 1

Note 1:

Oracle provides as a part of its Operating System (Oracle Linux, and Solaris) an interface to send commands to attached storage devices. This interface permits issuing commands to trigger secure data deletion

All Oracle storage devices respond to the Operating system commands in any one of the following ways, to comply with the 'secure data deletion' requirement.

1. Overwriting all User blocks of data using write commands
2. Sanitize command - removing reference to User data blocks
3. Key deletion command- Changing encryption keys

In cases where Overwrite of the specific block is either not possible or not supported, Sanitize & key deletion will be used to accomplish the secure deletion intent of the regulation.