



Fujitsu SPARC M12-2S Server

The Fujitsu SPARC M12-2S server is a flexible and scalable system based on the latest SPARC64 XII processor, delivering high performance and high availability for mission-critical enterprise workloads and cloud computing. The SPARC64 XII processor core is up to 2.5 times faster compared to previous-generation SPARC64 cores. Innovative Software on Chip capabilities deliver dramatic performance increases by implementing key software functions directly in the processor. The Fujitsu SPARC M12-2S system can scale from 1 to 8 processors using a modular architecture, with the flexibility to create a large, scale-up server or a scale-out configuration. In addition, customers can enjoy the benefits of Capacity on Demand with core-level activation, as well as physical partitioning capabilities and a suite of built-in virtualization technologies included at no cost.

PRODUCT OVERVIEW

Flexibility and Scalability for Mission-Critical Clouds

The Fujitsu SPARC M12-2S server offers high reliability and outstanding processor core performance, and has flexible scalability by virtue of a modular, building-block expansion methodology. The Fujitsu SPARC M12-2S server can scale up to 8 processors and 768 threads*, or it can be used in scaled-out configurations for parallel distributed processing. It is an ideal server for traditional enterprise-class workloads such as large-scale online transaction processing (OLTP), business intelligence and data warehousing (BI/DW), enterprise resource planning (ERP), and customer relationship management (CRM), as well as new environments in cloud computing or big data processing.



Key Benefits

- Scalability and performance for large ERP, BI/DW, SCM, CRM, big data, and analytics workloads
- Efficient consolidation of a large number of applications with diverse requirements on a single server
- High availability to support the most demanding 24/7 mission-critical applications
- Dramatic acceleration of Oracle Database In-Memory performance with new SPARC64 XII processor's Software on Chip capabilities
- Fast and economical system capacity growth in small increments with no downtime

* The Fujitsu SPARC M12-2S server is designed with capability to scale up to 6 building blocks, with up to 12 CPUs, up to 1,152 threads, up to 18 TB of main memory, up to 48 PCI Express slots, up to 6 physical partitions, and up to 368 PCI Express slots with optional PCI expansion unit. Please consult your Oracle sales or Oracle Partner Network sales representative about availability of such configuration.

The Fujitsu SPARC M12 servers incorporate the SPARC64 XII (“twelve”) processor that features improved throughput performance with eight threads per core, and significantly faster memory access through the use of DDR4 memory. Moreover, the Fujitsu SPARC M12 server delivers dramatic in-memory database performance increases by implementing key software processing functions onto the processor itself, a functionality called Software on Chip.

Mainframe-Class RAS and Maximum Scalability

The Fujitsu SPARC M12-2S server delivers high availability to support the most demanding mission-critical applications. It comes with mainframe-class reliability, availability, and serviceability (RAS) features, including automatic recovery with instruction retry, extended error-correcting code (ECC) protection, guaranteed data path integrity, configurable memory mirroring, and many more RAS capabilities. Furthermore, major system components are redundant and hot swappable for increased availability and serviceability.

The Fujitsu SPARC M12-2S server utilizes a modular architecture that can create a large, scale-up system configuration. An entry configuration can start with a single SPARC64 XII 12-core processor in a one server chassis—or building block—which can be expanded to two processors. The system can be further expanded incrementally from 1 to up to 4 building blocks, or up to 8 processors and 96 cores*. The building blocks are connected via a Fujitsu-developed interconnect technology that ensures high bandwidth, low latency, and linear scalability. The server also can be flexibly deployed and operated in a scale-out configuration, such as in a compute cluster.

In either scale-up or scale-out configuration, adding resources such as processors, memory, and PCIe expansion slots is a matter of gradually installing additional building blocks and connecting them via the high-speed interconnect. For example, the minimum configuration of one building block can be used for development and testing, and later more building blocks can be added to increase capacity when it’s time for deployment.

Oracle Solaris: the World’s Most Advanced Enterprise Operating System

Only Oracle offers the Oracle Solaris binary application guarantee, with guaranteed binary and source-code compatibility for legacy applications. The Fujitsu SPARC M12-2S server supports Oracle Solaris 11 and 10, which offer the powerful Oracle Solaris ZFS file systems, and unmatched capabilities such as dynamic tracing (DTrace feature of Oracle Solaris), cryptographic infrastructure, user and process rights management, and the Oracle Solaris IP Filter feature. In addition, Oracle Solaris 9 and 8 are supported using Oracle Solaris Legacy Containers.

Advanced Virtualization and Consolidation

SPARC-based servers are the industry’s best consolidation and virtualization platforms. The Fujitsu SPARC M12-2S server supports as many as 4 physical partitions*, and Oracle VM Server for SPARC software enables as many as 256 logical domains to be deployed in each physical partition. Physical partitions or logical domains can be further virtualized with Oracle Solaris Zones, which supports thousands of virtual machines, enabling massive server consolidation and virtualization.

- Higher levels of system utilization with flexible configurations and virtualization

Key Features

- The SPARC64 XII processor core is up to 2.5 times faster than previous-generation SPARC64 X+ processor cores.
- Dynamic scaling from 1 building block up to 4 building blocks with 8 processors and 96 cores
- Up to 48 TB of memory for large in-memory applications
- Mainframe-class RAS features, and on-line upgrades and servicing
- Software on Chip database acceleration on the SPARC64 XII processor
- Per core activation allows granular and agile response to changes in business requirements
- Layered virtualization includes Oracle VM Server for SPARC and Oracle Solaris Zones technologies
- New Vapor and Liquid Loop Cooling (VLLC) is three times more efficient than traditional cooling technology
- Server management is done through the independent service processor’s eXtended System Control Facility (XSCF).

* The Fujitsu SPARC M12-2S server is designed with capability to scale up to 6 building blocks, with up to 12 CPUs, up to 1,152 threads, up to 18 TB of main memory, up to 48 PCI Express slots, up to 6 physical partitions, and up to 368 PCI Express slots with optional PCI expansion unit. Please consult your Oracle sales or Oracle Partner Network sales representative about availability of such configuration.

FUJITSU SPARC M12-2S SERVER SPECIFICATIONS

Processor

Cache per Processor

- Level 1: instruction: 64 KB; data: 64 KB per core
- Level 2: 512 KB per core
- Level 3: 32 MB per processor

System Configuration

System Architecture

- SPARC V9 architecture, ECC protected

INTERFACES

- Network per unit: Four 10 GbE (100 Mb/sec, 1 Gb/sec, 10 Gb/sec), IEEE

- PCI Expansion Units per unit:
 - 1 CPU: Up to 48 slots (with four PCI expansion units connected)
 - 2 CPUs: Up to 88 slots (with eight PCI expansion units connected)
- Ports per unit: Two external USB (one front USB 2.0 and one rear USB 3.0)
- Administration interface per unit: two 1000Base-T (RJ45) network ports,

MASS STORAGE AND MEDIA

POWER SUPPLIES

KEY RAS FEATURES

SOFTWARE

Operating System

Oracle recommends the latest version of Oracle Solaris 11.4 for enhanced performance and functionality, including features enabled by Software on Chip technology

Software Included

Virtualization

ENVIRONMENT

Nonoperating temperature:

- -25° C to 60° C (-13° F to 140° F) (packed)
- 0 to 50° C (32° F to 122° F) (nonpacked)

Operating relative humidity: 20% to 80% relative humidity, noncondensing

Nonoperating relative humidity: 8 to 80% relative humidity, noncondensing

Operating altitude: 0 m to 3,000 m (0 feet to 9,840 feet)

DESCRIPTION	ONE CPU INSTALLED	TWO CPUS INSTALLED
Sound power level	8.2 B	8.5 B
Sound pressure level	64 dB	68 B

REGULATIONS (MEETS OR EXCEEDS THE FOLLOWING REQUIREMENTS)

Safety:

- UL/CSA 60950-1, UL/CSA 62368-1, EN EN 62368-1, IEC 60950-1, and IEC
- Emissions: FCC 47 CFR 15, ICES-003, EN 55032, KN32, EN 61000-3-2, EN 61000-3-3, JIS C 61000-3-2
- Immunity: EN 55035, KN35

Certifications:

- North America Safety (NRTL), CE(European Union), UKCA (United Kingdom), International CB Scheme, BSMI (Taiwan), RCM (Australia), KC (Korea), VCCI (Japan), EAC (Eurasian CU), BIS(India) ,

European Union directives:

- Restriction of Hazardous Substances (RoHS) Directive 2011/65/EU as amended, Low Voltage Directive 2014/35/EU, EMC Directive 2014/30/EU, WEEE Directive 2012/19/EU and Eco design Directive 2009/125/EC

All standards and certifications referenced are to the latest official version. For additional detail, please contact your sales representative.

Other country regulations/certifications may apply.

DIMENSIONS AND WEIGHT

- Per unit
 - Height: 175 mm (6.9 inches); 4U
 - Width: 440 mm (17.3 inches)
 - Depth: 800 mm (31.5 inches)
 - Weight: 60 kg (133 lb.)
- Per rack
 - Height: 2000 mm (78.7 inches)
 - Width: 700 mm (27.6 inches)
 - Depth: 1050 mm (41.3 inches)
 - Weight: 780 kg (1720 lb.)

WARRANTY

The Fujitsu SPARC M12-2 server comes with a one-year warranty. Visit oracle.com/us/support/policies/ for more information about Oracle's hardware warranty.

COMPLETE SUPPORT

With Oracle Premier Support, you will get the services you need to maximize the return on your investment in the Fujitsu SPARC M12-2 server. Complete system support includes 24/7 hardware service, expert technical support, proactive tools, and updates to Oracle Solaris, Oracle VM, and integrated software (such as firmware)—all for a single price. Learn more at oracle.com/support

CONNECT WITH US

Call +1.800.ORACLE1 or visit oracle.com.
Outside North America, find your local office at oracle.com/contact.

 blogs.oracle.com

 facebook.com/oracle

 twitter.com/oracle

Copyright © 2023, Oracle and/or its affiliates. All rights reserved. This document is provided for information purposes only, and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document, and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group. 0120

Disclaimer: This document is for informational purposes. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, timing, and pricing of any features or functionality described in this document may change and remains at the sole discretion of Oracle Corporation.

