

# StorageTek LTO Ultrium Data Cartridges



The high capacity and durability of Oracle's StorageTek Linear Tape Open (LTO) Ultrium data cartridges help you economically meet ever-increasing data storage requirements. With native capacity of up to 18.0 TB, StorageTek LTO Ultrium data cartridges are ideal for use in your archiving and backup applications. StorageTek LTO Ultrium data cartridges have high data integrity and longevity, so data is securely retained over its archived life. Backup and restore activities are accelerated, because more data is processed in less time with fewer tape mounts and dismounts.

## KEY FEATURES

- **Increased capacity.** StorageTek LTO Ultrium data cartridges provide higher capacity, which means fewer cartridges to buy and maintain, fewer tape mounts, and improved overall automation efficiency.
- **Data security.** StorageTek LTO Ultrium data cartridges are compatible with StorageTek LTO tape drives, which offer device-level data encryption to ensure data privacy and reduce the risk of data loss.

## Advanced Technology

StorageTek LTO Ultrium data cartridges feature a wide range of innovative technology advancements, including

- Highly reliable metal particle (Ultrium 5, Ultrium 6) and barium ferrite (Ultrium 7, Ultrium8, Ultrium9) media, with improved long-term magnetic stability for archival applications
- Non-contact 16 KB cartridge memory, which enables storage of historical usage records, indexing, and high-speed data searches by the drive
- Hardware-based AES 256-bit encryption capability of StorageTek LTO tape drives offers a high level of security during data storage and when transporting sensitive information

## Engage the Storage Experts

Oracle service professionals help you address storage challenges by delivering integrated services and solutions that optimize and manage storage performance over the life of your data. Oracle's recognized, world-class service and customer care give you confidence that your technology investment is protected and that your business will be responsive to change. Oracle's storage service professionals can help you gain and sustain measurable results with the reliability and flexibility that you require. In addition, you can make your storage solution decisions even stronger with one of the largest selections of high-performance tape media in the industry.

## STORAGETEK LTO ULTRIUM DATA CARTRIDGE SPECIFICATIONS

Basic Specifications	StorageTek LT09 Data Cartridge	StorageTek LT08 Data Cartridge	StorageTek M8-8 Data Cartridge	StorageTek Ultrium 7 Data Cartridge	StorageTek Ultrium 6 Data Cartridge	StorageTek Ultrium 5 Data Cartridge	StorageTek Ultrium Universal Cleaning Cartridge
Capacity, native (uncompressed)	18 TB	12 TB	9 TB	6.0 TB	2.5 TB	1.5 TB	N/A
Tape length	1035 m	960 m	960 m	960 m	846 m	846 m	319 m
Number of tracks	8960	6656	5376	3584	2176	1280	N/A
Tape width	12.65 mm	12.65 mm	12.65 mm	12.65 mm	12.65 mm	12.65 mm	12.65 mm
Tape thickness	5.2 µm	5.6 µm	5.6 µm	5.6 µm	6.4 µm	6.4 µm	8.9 µm
Expected Archival Tape Life	>30 years	>30 years	>30 years	>30 years	>30 years	>30 years	N/A
Cartridge color	Green	Burgundy	Purple	Purple	Black	Red	Black

## Environmental

	StorageTek LT09 Drive		StorageTek LT08, M8-8, Ultrium 7, Ultrium 6, Ultrium 5 Drives
Operating Mode (recommended)	+59°F to +77°F (+15°C to +25°C) 20% – 50% RH (non-condensed) +72°F (+22°C) dew point	Operating Mode	+50°F to +113°F (+10°C to +45°C) 10% – 80% RH (non-condensed) +79°F (+26°C) wet bulb maximum
Operating Mode (allowable)	+59°F to +95°F (+15°C to +25°C) 20% – 50% RH (non-condensed) +72°F (+22°C) dew point	Short Term Storage	+61°F to +90°F (+16°C to +32°C) 20% – 80% RH (non-condensed) +79°F (+26°C) wet bulb maximum
Shipping	-9.4°F to +120.2°F (-23°C to +49°C) 5% – 80% RH (non-condensed) +18.8°F (+26°C) dew point	Archive Storage	+61°F to +90°F (+16°C to +32°C) 20% – 80% RH (non-condensed) +79°F (+26°C) wet bulb maximum
		Shipping	-9.4°F to +120.2°F (-23°C to +49°C)

## Compatibility Matrix

	LT09 Drive	LT08 Drive	Ultrium 7 Drive	Ultrium 6 Drive	Ultrium 5 Drive	Ultrium 4 Drive
LTO9 Cartridge	Read/write 18.0 TB	Not compatible	Not compatible	Not compatible	Not compatible	Not compatible
LTO8 Cartridge	Read/write 12.0 TB	Read/write 12.0 TB	Not compatible	Not compatible	Not compatible	Not compatible
M-8 Cartridge	Not compatible	Read/write 9.0 TB	Not compatible	Not compatible	Not compatible	Not compatible
Ultrium 7 Cartridge	Not compatible	Read/write 6.0 TB	Read/write 6.0 TB	Not compatible	Not compatible	Not compatible
Ultrium 6 Cartridge	Not compatible	Not compatible	Read/write 2.5 TB	Read/write 2.5 TB	Not compatible	Not compatible
Ultrium 5 Cartridge	Not compatible	Not compatible	Read-only	Read/write 1.5 TB	Read/write 1.5 TB	Not compatible
Ultrium 4 Cartridge	Not compatible	Not compatible	Not compatible	Read-only	Read/write 800 GB	Read/write 800 GB



CONTACT US

For more information about StorageTek LTO Ultrium Tape Cartridges, visit [oracle.com/goto/tape](http://oracle.com/goto/tape) or call +1.800.ORACLE1 to speak to an Oracle representative.

CONNECT WITH US

 [blogs.oracle.com/oracle](https://blogs.oracle.com/oracle)

 [facebook.com/oracle](https://facebook.com/oracle)

 [twitter.com/oracle](https://twitter.com/oracle)


 [oracle.com](http://oracle.com)

## Integrated Cloud Applications & Platform Services

Copyright © 2022, Oracle and/or its affiliates. All rights reserved. This document is provided for information purposes only, and the contents hereof are subject to change without notice. This document is not warranted to be error-free, nor subject to any other warranties or conditions, whether expressed orally or implied in law, including implied warranties and conditions of merchantability or fitness for a particular purpose. We specifically disclaim any liability with respect to this document, and no contractual obligations are formed either directly or indirectly by this document. This document may not be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without our prior written permission.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.0116

 Oracle is committed to developing practices and products that help protect the environment